



INCLUDED ITEMS		ITEM	DESCRIPTION	QTY
1				0
2				1

PR-AD-48-xxx-xxZxHQ		TUBE DIA	48.6 mm
		INTERLOCK	MICRO-V HUB
		MOTOR END	NON THREADED HEX SHAFT
		IDLER END	SPRING LOADED HEX
		CONNECTOR	JST (S) OR M8 (M)

Unless otherwise specified upon order, Customer Required Clearance is automatically set to 2 mm by Pulseroller USA Order Entry System

xxx = RL in mm
xx = Speed Code



REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET
D	24-JAN-2023	COMBINED JST & AI INTO ONE DWG. UPDATED DWG NUMBER

REV.	DATE	DESCRIPTION
✓		

TITLE:	DATE:	DESIGNED BY:	CHECKED BY:	SCALE:	SHEET:
STANDARD 48 DIA MICRO-V PART NUMBER PR-AD-48-xxx-xxZxHQ	21-MAR-2014			NONE	1 OF 1

FOR:	DWG. NO.:	REV.:
SENERGY MOTOR ROLLER PULSEROLLER STANDARDS	PR-AD-48-xxx-xxZxHQ	D